

WITH THE POWER OF NATURAL d-LIMONENE

This thick-bodied formula contains natural d-Limonene solvent for the most powerful degreasing action available. It is designed to cling to vertical surfaces for maximum cleaning performance with no waste with run-off. Contains special emulsifiers so that loosened deposits are easily flushed off with hot or cold water, leaving surfaces sparkling clean and free of residue. Deodorizes as it cleans, too!

This heavy duty gel degreaser removes grease, tar, pitch, oil, asphalt, roofing compounds from tools, forms and brick, stone and masonry surfaces. It quickly strips thick and stubborn deposits from asphalt spreaders, rollers and other road construction machinery, also heating pots, paddles, buckets, brooms, shovels and other tools. Ideal for removing heavy, trodden deposits from concrete floors.

Use it to clean engine blocks, frames, transmissions and other truck, bus, auto and construction machinery parts. Excellent for degreasing 5th wheels of tractors.

This product contains	CAS Number
d-Limonene	5989-27-5
Mineral Spirits	8052-41-3
Poly(oxyethylene) octylphenol	9002-93-1
Ethylene glycol	107-21-1



WITH THE POWER OF NATURAL d-LIMONENE

THICK CLINGING EMULSIFIABLE DEGREASER

CAUTION – COMBUSTIBLE

May be harmful if swallowed. Keep away from heat or open flame. See side panel for additional precautions and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

**Western Environmental
Services, Inc.**

“It’s not just our planet, it’s our home!”

TO ORDER CALL TOLL FREE 1-800-574-3948

Visit us today at www.western-environmental.com

THICK CLINGING FORMULA

DIRECTIONS:

Spray, mop or brush the gel degreaser onto the area or part to be cleaned. Allow to penetrate for 10 to 15 minutes then flush away the loosened deposits with a pressure spray of hot or cold water. Scrubbing with a stiff brush will speed removal of heavy accumulations of grease and grime. Rinse sprayers or other application equipment immediately after use.

This degreaser gel will not harm most vehicle paints or lettering, but always test a small area of the surface in an inconspicuous area before using. Do not apply to plastic parts, including distributors caps.

CAUTION – COMBUSTIBLE

May be harmful if swallowed. Contains petroleum distillates. Keep away from heat or open flame. Avoid breathing vapors. Use with adequate ventilation. Avoid contact with eyes and mucus membranes. Avoid prolonged or repeated contact with skin.

FIRST AID:

External – Flush with water.

Internal – Do NOT induce vomiting. Give person several glasses of water. Call a physician immediately.

Eyes – Flush eyes and under eyelids with cool water for at least 15 minutes. If irritation persists, obtain medical attention.

KEEP OUT OF REACH OF CHILDREN

38891883

NET CONTENTS:

☐ 5 ☐ 6 ☐ 20 ☐ 30 ☐ 55

GALLONS: