

This powerful solvent cleaner and degreaser has a high dielectric strength that makes it ideal for use around energized electrical equipment. Its non-flammable nature makes it perfect for use in areas where reduced fire hazard is important.

Dielectric Strength (ASTM-D-877-80): **30 KV**

To clean electric motors in place, spray directly into the motor to flush out grease, carbon, dust, etc. Run motor until dry, then re-lubricate.

Motor may also be submerged in clean solvent and turned on for 3 to 5 minutes. Turn off current, remove motor from tank and allow to air dry thoroughly. Re-lubricate before use. Use only clean solvent to prevent damage from grit.

Electrical switches, fuse panels, contact points, printed circuits may be safely cleaned with this product. For extra safety, always disconnect power source before handling electrical devices.

This clean, powerful solvent degreases a wide variety of surfaces. Safe for use on all types of metal including aluminum, stone, concrete, fiberglass, painted surfaces and many plastics. Test before using on plastics.



**CLEAN, FAST DRYING
COLD SOLVENT
DEGREASER**

CAUTION - VAPOR HARMFUL

Harmful if swallowed. Eye and skin irritant.
See side panel for further cautions
and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

***Western Environmental
Services, Inc.***

"It's not just our planet, it's our home!"
TO ORDER CALL TOLL FREE 1-800-574-3948
Visit us today at www.western-environmental.com

Flushes grease and brake fluid from brake shoes and calipers. Strips grime from machinery and engines. Removes ink, lint and grease from the rollers and printing presses, also adding machines and typewriters. Cleans and de-waxes packaging machinery and vending machines – anywhere fast, clean degreasing is required.

DO NOT HEAT THIS PRODUCT – USE COLD.

CAUTION - VAPOR HARMFUL

Harmful if swallowed. Eye and skin irritant. Use with adequate ventilation. Avoid prolonged breathing of vapor or fumes. Do not take internally. Avoid contact with skin, eyes and mucous membranes.

FIRST AID:

If Inhaled: Remove person to fresh air. Perform artificial respiration as indicated. Obtain immediate medical assistance.

If Swallowed: Give person several glasses of water and induce vomiting. Obtain medical assistance.

If In Eyes: Flush with plenty of cool water for at least 15 minutes. Obtain medical assistance.

If On Skin: Wash with soap and water. If irritation persists, obtain medical assistance.

KEEP OUT OF REACH OF CHILDREN

This product contains: Trichloroethylene	CAS Number: 79-01-6
--	-------------------------------

31092727

NET CONTENTS:

☐ 5 ☐ 6 ☐ 20 ☐ 30 ☐ 35 ☐ 55
GALLONS