MATERIAL SAFETY DATA SHEET

Western Environmental Services, Inc.

P.O. Box 9035

Scottsdale, AZ 85252

GENERAL INFORMATION NUMBER: (602) 234-8873 REVISION DATE: October 3, 2002

DATE OF ISSUE: July 16, 2004

I - Product Identification

Kleen Kut

PRODUCT CODE: 0303

CHEMICAL FORMULATION: Synthetic cutting fluid.

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0 HAZARD RATING: 4 - Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

II - Hazardous Ingredients

· ·							
	Values reported as TWA unless noted.						
	APPROX	OSHA	ACGIH	EPA 40 CFR:			
SUBSTANCE	<u>%</u>	<u>PEL</u>	<u>TLV</u>	<u>302</u>	<u>355</u>	<u>372</u>	<u>CAS #</u>
Triethanolamine	1.00-10.0	N/E	N/E	N	N	N	102-71-6
Alkanolamine	1.00-10.0	N/E	N/E	N	N	N	Mixture
Diethanolamine	< 2.00	3 ppm	$2 \text{ mg/m}^3 \text{ (skin)}$	Y	N	Y	111-42-2

Key: PEL: Permissible Exposure Limit
N/A: Not Applicable

TLV: Threshold Limit Value
C: Ceiling level
STEL: Short Term Exposure Limit
N/B: Not Established
Y: Yes
N: No

N/A: Not Applicable N/D: Not Determined N/E: Not Established 302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).

355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).

372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

BOILING POINT (°F): N/D

VAPOR PRESSURE (mm Hg): N/D

VAPOR DENSITY (AIR = 1): N/D

VAPOR DENSITY (AIR = 1): N/D

EVAPORATION RATE (WATER = 1): N/D

SOLUBILITY IN WATER: Soluble pH: 9.50-10.20

APPEARANCE AND ODOR: Clear, golden-brown liquid, slight odor.

IV - Fire and Explosion Hazard Data

FLASH POINT (${}^{\circ}$ F): > 200 (TEST METHOD):

FLAMMABLE LIMITS IN AIR (VOLUME %)

UPPER: N/D

LOWER: N/D

EXTINGUISHING MEDIA: Water, foam, carbon dioxide, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water fog. Firefighters should be equipped with full protective gear including self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARD: None

V - Reactivity Data

STABILITY: Stable

INCOMPATIBILITY: Acids and strong oxidizers.

CONDITIONS TO AVOID: None

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce oxides of carbon and nitrogen.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None

VI - Health Hazard Data

ROUTES OF ENTRY INHALATION: EYE CONTACT: X SKIN CONTACT: X INGESTION: X INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS: None

EFFECTS OF OVEREXPOSURE

IF IN EYES: Moderate to severe irritation, tearing and redness. Possible corneal injury.

IF ON SKIN: Irritation and redness with prolonged exposure.

IF SWALLOWED: Irritation of gastrointestinal tract, nausea, vomiting.

IF INHALED: May cause irritation to respiratory tract, dizziness.

EMERGENCY AND FIRST AID PROCEDURES

IF IN EYES: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

IF ON SKIN: Wash with soap and water. If irritation persists, obtain medical attention.

IF SWALLOWED: Contact physician or poison control center immediately. Give affected person 1 to 2 glasses of water. Do not induce vomiting unless told to do so by a physician or poison control center. Never give anything by mouth to an unconscious person.

IF INHALED: Remove person to fresh air. If irritation persists, obtain medical attention.

VII - Spill or Leak Protection

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Ventilate area and remove all sources of ignition. Contain spill. Soak up spilled material with inert absorbent material and place in a properly marked closed container for proper disposal.

WASTE DISPOSAL METHOD: Consult local environmental authorities.

VIII - Special Protection Information

RESPIRATORY PROTECTION: Use with adequate ventilation. Do not breathe vapors or mists. If recommended Exposure Limits are exceeded wear a NIOSH approved respirator, following manufacturer's recommendations.

VENTILATION LOCAL: Recommended MECHANICAL: Not required

PROTECTIVE GLOVES: Chemical resistant.

EYE PROTECTION: Safety glasses.

OTHER PROTECTIVE EQUIPMENT: Protective clothing.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place away from heat or open flame. Keep container tightly closed when not in use. Keep away from acids.

OTHER PRECAUTIONS: Keep out of reach of children.

IX - Transportation Information (ground transportation only)

DOT PROPER SHIPPING NAME: None

DOT CLASS: None **DOT ID NUMBER:** None **DOT PACKING GROUP:** None

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

REVISION DATE: October 3, 2002 Prepared by: PMR DATE OF ISSUE: July 16, 2004

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Western Environmental Services, Inc. assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.