

This new surface conditioner and primer changes rust into a dark protective polymeric coating. It converts existing rust to an inert coating that seals out moisture to prevent future rust and corrosion. This rust converter provides an excellent primer coating for the application of quality oil-based paints. Surfaces protected with this primer and an oil-based paint system resists the effects of weather, rain, sun and salt spray without peeling or cracking. This easy-to-use product is the first step in providing long-term protection of steel and iron surfaces.

DIRECTIONS FOR USE

SURFACE PREPARATION: Remove large rust and scale particles with a wire brush or sandpaper. Clean the surface thoroughly to remove dirt, dust and grease.

APPLICATION: SHAKE OR STIR WELL BEFORE USING! Apply this product using a brush or roller. This product is ready-to-use – NO thinning is required.

COVERAGE: 500 square feet per gallon on a smooth, non-porous surface. Irregular, porous or textured surfaces may require more product.

DRYING TIME: The resulting coat will dry to a smooth, dark finish in 20 minutes. Apply a second coat to ensure complete transformation of rusty surfaces. Allow 48 hours of cure time before the application of the finished paint coat.

For long-lasting protection of iron surfaces, the cured rust converter coating should be sealed with two coats of a high quality oil-based paint. No other primer is required.



HALTS EXISTING RUST
AND PREVENTS FUTURE
CORROSION WITH A DURABLE
PROTECTIVE BARRIER

NO NEED FOR SAND BLASTING,
GRINDING OR SCRAPING

CAUTION

Harmful if swallowed. Eye irritant.
See side panel for further cautions
and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

**Western Environmental
Services, Inc.**

"It's not just our planet, it's our home!"
TO ORDER CALL TOLL FREE 1-800-574-3948
Visit us today at www.western-environmental.com

CLEAN-UP: Application equipment should be cleaned immediately with soap and water.

GENERAL: Do not apply this product if the surface temperatures are below 50°F. Store in a cool, dry place, protected from freezing or temperatures above 100°F.

*IMPORTANT: DO NOT RETURN UNUSED
MATERIAL TO ORIGINAL CONTAINERS.*

CAUTION

Harmful if swallowed. Avoid contact with eyes and mucous membranes. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. In case of spillage, absorb with inert material and dispose in accordance with applicable regulations.

FIRST AID

If In Eyes: Flush eyes and under eyelids with cool water for at least 15 minutes. Obtain medical attention.

If Swallowed: Give person several glasses of water and induce vomiting. Obtain medical assistance immediately.

If On Skin: Remove contaminated clothing and laundry before re-use. Wash out product quickly with soap and water.

If Inhaled: If breathing difficulty is observed, remove person to fresh air.

KEEP OUT OF REACH OF CHILDREN

This product contains:		CAS Number:
Proprietary Polymer	No CAS Number
Water7732-18-5
Tannic acid1401-55-4
2-Butoxyethanol111-76-2
Synthetic Smectite53320-86-8

0346.082400

NET CONTENTS:

☐ 5 ☐ 6 ☐ 20 ☐ 30 ☐ 55
GALLONS